Current version: 2.4.0, issued: 11.04.2019 Reglaced version: 2.3.0, issued: 04.01.2019 Region: GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

#### **Armaflex Cleaner**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

designed for cleaning surfaces/substrates before applying Armaflex glues and cleaning tools (except Armaflex SF990 and Armaflex Ultima SF990)

#### Uses advised against

No data available.

#### 1.3 Details of the supplier of the safety data sheet

#### **Address**

Armacell GmbH

Robert-Bosch-Straße 10 48153 Münster

Telephone no. +49 (0) 251 - 7603-200 Fax no. +49 (0) 251 - 7603-561 e-mail info.de@armacell.com

#### Information provided by / telephone

Dr. Heribert Quante, Tel.: +49 (0) 251 - 7603-227

## Advice on Safety Data Sheet

heribert.quante@armacell.com

## 1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336

## Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008: Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

## 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

## Hazard pictograms





GHS02

Signal word

Hazardous component(s) to be indicated on label:

ethyl-acetate

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Current version: 2.4.0, issued: 11.04.2019 Reglaced version: 2.3.0, issued: 04.01.2019 Region: GB

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container to a facility in accordance with local and national regulations.

#### 2.3 Other hazards

Vapours can form an explosive mixture with air.

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable. The product is not a substance.

#### 3.2 Mixtures

Hazardous ingredients

No	Substance name		Additio	nal info	rmatio	on	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration		%		
1	ethyl-acetate						
	141-78-6	EUH066	>=	70.00	- <	90.00	%-b.w.
	205-500-4	Eye Irrit. 2; H319					
	607-022-00-5	Flam. Liq. 2; H225					
	01-2119475103-46	STOT SE 3; H336					
2	butanone						
	78-93-3	Eye Irrit. 2; H319	>=	10.00	- <	25.00	%-b.w.
	201-159-0	Flam. Liq. 2; H225					
	606-002-00-3	STOT SE 3; H336					
	01-2119457290-43						
3	Hydrocarbons, C6-C7	, isoalkanes, cyclics, <5% n-hexane					
	64742-49-0	Aquatic Chronic 2; H411	>=	5.00	- <	10.00	%-b.w.
	926-605-8	Asp. Tox. 1; H304					
	-	Flam. Liq. 2; H225					
L	01-2119486291-36	STOT SE 3; H336					

Full Text for all H-phrases and EUH-phrases: pls. see section 16

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

When inhaled remove to fresh air and seek medical aid.

#### After skin contact

When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Seek medical advice immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

#### **Symptoms**

Irritating to eyes, respiratory system and skin. breath difficulties; Coughing; Dazyness; Dizziness; Headache; Nausea; reddening of the skin; blistering

Current version: 2.4.0, issued: 11.04.2019 Reglaced version: 2.3.0, issued: 04.01.2019 Region: GB

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray jet; Carbon dioxide; Dry chemical extinguisher; Foam

#### Unsuitable extinguishing media

High power water jet

#### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Exclude sources of ignition and ventilate the area. Do not inhale vapours. Ensure adequate ventilation. Use personal protective clothing. Avoid contact with skin, eyes and clothing.

#### For emergency responders

Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

## 6.4 Reference to other sections

No data available.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

## Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary).

## General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Wash hands before breaks and after work. Do not inhale vapours. Avoid contact with eyes and skin.

## Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. Take precautionary measures against static charges. No sparking tools should be used

## 7.2 Conditions for safe storage, including any incompatibilities

## Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

#### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

## Advice on storage assembly

Substances to be avoided, pls. See chapter 10.

#### 7.3 Specific end use(s)

No data available.

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	ethyl-acetate	141-78-6		205-500-4	
	2017/164/EU				
	Ethyl acetate				
	WEL short-term (15 min reference period)	1468	mg/m³	400	ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m³	200	ppm
	List of approved workplace exposure limits (WELs) / EH40				
	Ethyl acetate				
	WEL short-term (15 min reference period)			400	ppm
	WEL long-term (8-hr TWA reference period)			200	ppm
2	butanone	78-93-3		201-159-0	
	2000/39/EC				
	Butanone				
	WEL short-term (15 min reference period)	900	mg/m³	300	ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m³	200	ppm
	List of approved workplace exposure limits (WELs) / EH40				
	Butan-2-one				
	WEL short-term (15 min reference period)	899	mg/m³	300	ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m³	200	ppm
	Comments	Sk, BMGV			
3	n-hexane	110-54-3		203-777-6	
	2006/15/EC				
	n-Hexane	1			
	WEL long-term (8-hr TWA reference period)	72	mg/m³	20	ppm
	List of approved workplace exposure limits (WELs) / EH40				
	n-Hexane	T	<u> </u>		
	WEL long-term (8-hr TWA reference period)	72	mg/m³	20	ppm
4	cyclohexane	110-82-7		203-806-2	
	2006/15/EC				
	Cyclohexane	1 700	/ 2	000	
	WEL long-term (8-hr TWA reference period)	700	mg/m³	200	ppm
	List of approved workplace exposure limits (WELs) / EH40				
	Cyclohexane	1,050	/ 2	000	
	WEL short-term (15 min reference period)	1050	mg/m³	300	ppm
	WEL long-term (8-hr TWA reference period)	350	mg/m³	100	ppm

## **DNEL, DMEL and PNEC values**

DNEL values (worker)

No	Substance name			CAS / EC n	0
	Route of exposure	Exposure time	Effect	Value	
1	ethyl-acetate	•		141-78-6 205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Short term (acut)	systemic	1468	mg/m³
	inhalative	Long term (chronic)	local	734	mg/m³
	inhalative	Short term (acut)	local	1468	mg/m³
	inhalative	Long term (chronic)	systemic	734	mg/m³
2	butanone			78-93-3 201-159-0	-
	dermal	Long term (chronic)	systemic	1161.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	600.00	mg/m³
}	Hydrocarbons, C6-C7, is	soalkanes, cyclics, <5% n-hex	ane	64742-49-0 926-605-8	
	dermal	Long term (chronic)	systemic	773	mg/kg/day
	inhalative	Long term (chronic)	systemic	2035	mg/m³

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

## **DNEL** value (consumer)

No	Substance name			CAS / EC r	10
-110	Route of exposure	Exposure time	Effect	Value	
1	ethyl-acetate	, , , , , , , , , , , , , , , , , , , ,		141-78-6 205-500-4	
	oral	Long term (chronic)	systemic	4.5	mg/kg/day
	dermal	Long term (chronic)	systemic	37	mg/kg/day
	inhalative	Short term (acut)	systemic	734	mg/m³
	inhalative	Long term (chronic)	local	367	mg/m³
	inhalative	Short term (acut)	local	734	mg/m³
	inhalative	Long term (chronic)	systemic	367	mg/m³
2	butanone			78-93-3 201-159-0	
	oral	Long term (chronic)	systemic	31.00	mg/kg/day
	dermal	Long term (chronic)	systemic	412.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	106.00	mg/m³
3	Hydrocarbons, C6-C7, iso	alkanes, cyclics, <5% n-hex	ane	64742-49-0 926-605-8	
	oral	Long term (chronic)	systemic	699	mg/kg/day
	dermal	Long term (chronic)	systemic	699	mg/kg/day
	inhalative	Long term (chronic)	systemic	603	mg/m³

#### **PNEC** values

	PNEC values			
No	Substance name		CAS / EC n	0
	ecological compartment	Туре	Value	
1	ethyl-acetate		141-78-6	
			205-500-4	
	water	fresh water	0.24	mg/L
	water	marine water	0.024	mg/L
	water	Aqua intermittent	1.65	mg/L
	water	fresh water sediment	1.15	mg/kg dry weight
	water	marine water sediment	0.115	mg/kg dry weight
	soil	-	0.148	mg/kg dry weight
	sewage treatment plant	-	650	mg/L
	secondary poisoning	-	200	mg/kg
2	butanone		78-93-3	
			201-159-0	
	water	fresh water	55.80	mg/L
	water	marine water	55.80	mg/L
	water	Aqua intermittent	55.8	mg/L
	water	fresh water sediment	284.74	mg/kg
	with reference to: dry weight			
	water	marine water sediment	284.7	mg/kg
	with reference to: dry weight			
	soil	-	22.5	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	709	mg/L
	secondary poisoning	-	1000	mg/kg
	with reference to: food			

## 8.2 Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, local exhaust at the work station if necessary.

## Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of insufficient ventilation and during spray application respiratory protection necessary. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator

A-P2

## Eye / face protection

Tightly fitting safety glasses (EN 166).

Current version: 2.4.0, issued: 11.04.2019 Reglaced version: 2.3.0, issued: 04.01.2019 Region: GB

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material neoprene
Appropriate Material nitrile rubber

Material thickness > 0.7 mm
Breakthrough time > 60 min

Other

Chemical-resistant work clothes.

**Environmental exposure controls** 

No data available.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Form/Colour			
liquid			
colourless			
Odour			
of solvents			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
Value	appr.	70	°C
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value	appr.	-20	°C
Method	Cleveland closed cup		
Auto-ignition temperature			
Value		274	°C
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits		4	0/
Value		1	% vol
Upper flammability or explosive limits		10	
Value		13	% vol
Vapour pressure			
Value	<	1100 50	hPa °C
Reference temperature		50	C

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

appr.	0.9	g/cm³	
	20	°C	
	appr.	• • •	

No data available

Solubility(ies)

No data available

Part	Partition coefficient: n-octanol/water							
No	Substance name		CAS no.		EC no.			
1	ethyl-acetate		141-78-6		205-500-4			
log F	Pow			6.8				
Refe	erence temperature			25	°C			
Sour	rce	ECHA						
2	butanone		78-93-3		201-159-0			
log F	Pow			0.3				
Refe	erence temperature			40	°C			
Meth	nod	OECD 117						
Sour	rce	ECHA						

Viscosity			
Value	<	21	mm²/s
Reference temperature		40	°C

## 9.2 Other information

Other information	
No data available.	

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

None, if handled according to order.

## 10.4 Conditions to avoid

None known

#### 10.5 Incompatible materials

strong oxidizing agents

### 10.6 Hazardous decomposition products

None, if handled according to intended use.

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

# SECTION 11: Toxicological information

# 11.1 Information on toxicological effects

Acut	te oral toxicity				
No	Substance name		CAS no.		EC no.
1	ethyl-acetate		141-78-6		205-500-4
LD50	)	>		5600	mg/kg bodyweight
Spec	cies	rat			
Sour	ce	ECHA			
2	butanone		78-93-3		201-159-0
LD50	)			3460	mg/kg bodyweight
Spec	cies	rat			
Meth	nod	OECD 423			
Sour	ce	ECHA			

Acute dermal toxicity						
No	Substance name		CAS no.		EC no.	
1	ethyl-acetate		141-78-6		205-500-4	
LD50	0	>		20000	mg/kg bodyweight	
Spec		rabbit ECHA				
2	butanone		78-93-3		201-159-0	
LD50	0	>		10	mg/kg bodyweight	
Spec	cies	rabbit				
Meth	nod	OECD 402				
Sour	rce	ECHA				

Acut	Acute inhalational toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane	64742-49-0		926-605-8	
LC50		>		25.2	mg/l	
Dura	tion of exposure			4	h	
State	e of aggregation	Vapour				
Spec	ties	rat				
Sour	ce	ECHA				

Skin	Skin corrosion/irritation					
No	Substance name		CAS no.		EC no.	
1	ethyl-acetate		141-78-6		205-500-4	
Spec	ies	rabbit				
Meth	od	OECD 404				
Sour	ce	ECHA				
Evalu	uation	low-irritant				
Evalu	uation/classification	Based on avail	able data, the clas	ssification crite	ria are not met.	
2	butanone		78-93-3		201-159-0	
Dura	tion of exposure			4	h	
Spec	ies	rabbit				
Meth	od	OECD 404				
Sour	ce	ECHA				
Evalu	uation	non-irritant				
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane	64742-49-0		926-605-8	
Spec	ies	rabbit				
Meth	od	OECD 404				
Sour	ce	ECHA				
Evalu	uation	irritant				

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

Serious eye damage/irritation					
No	Substance name	CAS no.	EC no.		
1	ethyl-acetate	141-78-6	205-500-4		
Spec	cies	rabbit			
Meth	nod	OECD 405			
Sour	ce	ECHA			
Eval	uation	low-irritant			
2	butanone	78-93-3	201-159-0		
Spec	cies	rabbit			
Method		OECD 405			
Sour	ce	ECHA			
Eval	uation	irritant			

Resp	Respiratory or skin sensitisation						
No	Substance name	CAS no.	EC no.				
1	ethyl-acetate	141-78-6	205-500-4				
Rout	e of exposure	Skin					
Spec	cies	guinea pig					
Meth	od	OECD 406					
Sour	ce	ECHA					
Eval	uation	non-sensitizing					
2	butanone	78-93-3	201-159-0				
Rout	e of exposure	Skin					
Spec	cies	guinea pig					
Meth	od	OECD 406					
Sour	ce	ECHA					
Eval	uation	non-sensitizing					

Gerr	n cell mutagenicity					
No	Substance name	CAS no.	EC no.			
1	butanone	78-93-3	201-159-0			
Spec	cies	Salmonella typhimurium				
Meth	nod	OECD 471				
Sour	ce	ECHA				
Eval	uation/classification	Based on available data, the class	Based on available data, the classification criteria are not met.			
2	Hydrocarbons, C6-C7, isoalkan	es, cyclics, <5% n-hexane 64742-49-0	926-605-8			
Rout	e of exposure	inhalational				
Туре	e of examination	Chromosome aberration test				
Spec	cies	rat				
Meth	nod	OECD 475				
Sour	ce	ECHA				

Repr	Reproduction toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5°	% n-hexane	64742-49-0		926-605-8	
Rout	e of exposure	inhalational				
NOA	EC			9000	ppm	
Type	of examination	2 generation s	tudy			
Spec	cies	rat				
Meth	od	OECD 416				
Sour	ce	ECHA				

Carc	Carcinogenicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane	64742-49-0		926-605-8	
Rout	e of exposure	inhalational				
NOA	EC			3000	ppm	
Spec	ries	rat				
Meth	od	OECD 451				
Sour	ce	ECHA				

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

STOT - single exposure	
No data available	
•	

0=0	OTOT manufacture and a second						
STO	STOT - repeated exposure						
No	Substance name		CAS no.		EC no.		
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane	64742-49-0		926-605-8		
Rout	e of exposure	inhalational					
NOA	EC			14000	mg/m³		
Dura	tion of exposure			8	h		
Spec	ries	rat					
Sour	ce	ECHA					

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of the vapours causes irritation of the respiratory tract and mucous membrane, headaches, nausea, giddiners, vomiting.

# SECTION 12: Ecological information

## 12.1 Toxicity

Toxi	city to fish (acute)			
No	Substance name	CAS no.		EC no.
1	ethyl-acetate	141-78-6		205-500-4
LC50			230	mg/l
Dura	tion of exposure		96	h
Spec	ries	Pimephales promelas		
Sour	ce	ECHA		
2	butanone	78-93-3		201-159-0
LC50			2993	mg/l
Dura	tion of exposure		96	h
Spec	ries	Pimephales promelas		
Meth	od	OECD 203		
Sour	ce	ECHA		
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane 64742-49-0		926-605-8
LL50			11.4	mg/l
Dura	tion of exposure		96	h
Spec	ries	Oncorhynchus mykiss		
Meth	od	OECD 203		
Sour	ce	ECHA		

# Toxicity to fish (chronic) No data available

TTO GALLA AVAILABLE						
Toxicity to Daphnia (acute)						
No Substance name	CAS r	10.	EC no.			
1 ethyl-acetate	141-78	8-6	205-500-4			
EC50		1350	mg/l			
Duration of exposure		48	h			
Species	Daphnia magna					
Source	ECHA					
2 butanone	78-93-	-3	201-159-0			
EC50		308	mg/l			
Duration of exposure		48	h			
Species	Daphnia magna					
Method	OECD 202					
Source	ECHA					
3 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane 64742	-49-0	926-605-8			
EL50		3	mg/l			
Duration of exposure		48	h			
Species	Daphnia magna					
Method	OECD 202					
Source	ECHA					

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

Toxio	Toxicity to Daphnia (chronic)				
No da	No data available				
Toxio	Toxicity to algae (acute)				
No	Substance name	CAS no.		EC no.	
1	butanone	78-93-3		201-159-0	
EC50	)		2029	mg/l	
Duration of exposure			96	h	
Species		Pseudokirchneriella subcapitata			
Method		OECD 201			
Sour	ce	ECHA			
2	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane 64742-49-0		926-605-8	
EL50			1030	mg/l	
Dura	tion of exposure		72	h	
Spec	ies	Raphidocelis subcapitata			
Meth	od	OECD 201			
Sour	ce	ECHA			

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

	Biodegradability					
No	Substance name		CAS no.		EC no.	
1	ethyl-acetate		141-78-6		205-500-4	
Source		ECHA				
Evalu	uation	readily biodeg	radable			
2	butanone		78-93-3		201-159-0	
Type		aerobic biodeg	gradation			
Value	e			98	%	
Duration				28	day(s)	
Meth	od	OECD 301 D				
Sour		ECHA				
Evalu	uation	readily biodeg	radable			
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5	% n-hexane	64742-49-0		926-605-8	
Туре		aerobic biodeg	gradation			
Value	9			98	%	
Dura	tion			28	day(s)	
Meth	od	OECD 301 F				
Sour		ECHA				
Evalu	uation	readily degrad	able			

12.3 Bioaccumulative potential

Part	Partition coefficient: n-octanol/water				
No	Substance name	CAS no	).	EC no.	
1	ethyl-acetate	141-78-	-6	205-500-4	
log F	Pow		6.8		
Reference temperature			25	°C	
Sour	ce	ECHA			
2	butanone	78-93-3		201-159-0	
log Pow			0.3		
Reference temperature			40	°C	
Method		OECD 117			
Source		ECHA			

## 12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment		
PBT assessment	The components of this product are not considered to be a PBT.	
vPvB assessment	The components of this product are not considered to be a vPvB.	

Current version: 2.4.0, issued: 11.04.2019 Replaced version: 2.3.0, issued: 04.01.2019 Region: GB

#### 12.6 Other adverse effects

No data available.

#### 12.7 Other information

#### Other information

Do not discharge product unmonitored into the environment.

Do not discharge into the drains or waters and do not store on public depositories

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

## **Packaging**

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## **SECTION 14: Transport information**

# 14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1993

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Technical name ethyl-acetate butanone
Special Provision 640 640D
Tunnel restriction code

Special Provision 640 640D
Tunnel restriction code D/E
Label 3

#### 14.2 Transport IMDG

Class 3 Packing group II UN number UN1993

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Technical name ethyl-acetate butanone

EmS F-E, S-E

Label 3

## 14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1993

Proper shipping name Flammable liquid, n.o.s.

Technical name ethyl-acetate butanone

Label 3

#### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

Current version: 2.4.0, issued: 11.04.2019 Reglaced version: 2.3.0, issued: 04.01.2019 Region: GB

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

#### Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

# Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII. No 3, 40

# Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is subject to Part I of Annex I, risk category: P5b

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)			
VOC content	<=900 g/l		
VOC content	100 %		

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture.

## **SECTION 16: Other information**

#### **Further information**

Authors responsible for the compilation of the material safety data sheet: UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de.

The information is based on our current knowledge however it does not represent a guarantee of product properties nor does it create any legal obligation.

## Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

## Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 636648